Dispersing drive Unidrive X 1000

A general-purpose dispersing drive unit, for a host of dispersing tasks with a wide speed-range from 4000 rpm to 33000 rpm.

Suitable for volumes from 0.2 ml (T 6) to 5000 ml (T/G 30).

Unidrive X 1000	Part No. 60402-50 230V/50 Hz Part No. 60402-51 115V/60 Hz
Power	1050 Watt
Motor output	650 Watt
Idle speed	4000 - 33000 Rpm
Dimensions W x D x H	75 x 75 x 300 mm,
Speed display	No
Weight	2,1 kg
Conditions of surroundings	
Admissible temp. of surrounding	+ 5°C up to + 40°C max. 80 % relative humidity
Permissible ON time	100%

Accessories:

	Description	**Part No.**
Pedestal stand incl. rod	platform overall dimensions: 330x200 mm, rod diameter: 16mm, length:690mm	60491-00
Cross over clamp	Casted alloy clamp to attach the unit to a stand	60492-00
Cross over clamp	Steel clamp to attach the unit to a stand	60492-50
Universal wrench	Universal rotor wrench for Shafts 6 - 30 mm	60470-00
Socket wrench	for all shafts	60471-00
Rotor wrench	only for shaft T 10	60472-00
Rotor wrench	for shaft T 17: use Universal wrench	60470-00
Rotor wrench	for shaft T 20/G 20	60473-00

Ingenieurbüro CAT M. Zipperer GmbH, Etzenbach 16, 79219 Staufen
Tel.: +49 (0)7636 78030, Fax: +49 (0)7636 780345, E-Mail: info@cat-ing.de

Ingenieurbüro CAT M. Zipperer GmbH, Etzenbach 16, 79219 Staufen
Tel.: +49 (0)7636 78030, Fax: +49 (0)7636 780345, E-Mail: info@cat-ing.de

T 30/G 30 only for short-term operation

T = Shaft with ETFE bearing. This shaft type is used for standard application. (For liquid media like water, oil, etc.) The bearing must be cooled by the media, which penetrates into the bearing.
A dry run is not permitted.

G = Shaft with slide seal ring. This shaft type is excellent for applications with aggressive respectively abrasive media and when pressure is applied. Also suitable for use with solids.
The bearing is sealed and suitable for dry running